

SUBMITTAL

This shower enclosure shall be model XSS 3637 BF 3P .625, right. Finished surface shall be of a sanitary grade applied acrylic. The base shall be attached to the sump in such a manner to form an integral part with an inner and outer coating of polyester resin. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of 40 1/4" x 38 1/4" x 77 5/8". The unit shall meet CSA B45.5-11, HUD-UM73, ADA, ANSI A117.1, and Home Innovation Research Lab.

HANDED BY THE VALVE

* For shower installation, L-grab bar must be removed so wall and base sections may be separated to apply caulking to seams.


The enclosure shall be equipped with the following accessories:
 1) One 18" x 33 1/2" x 1 1/4" diameter white horizontal L-grab bar, 2) One 24" x 1 1/4" diameter white vertical grab bar, both with 1 1/2" statute clearance, mounted with stainless steel bolts, and secured from the rear with 3" x 3" x 11 gauge metal mounting plates, 3) 32" x 21" white frameless HDPE fold up seat, 4) One inch diameter, 18 gauge white curtain rod with receiver cups, 5) Molded ledge on the back wall, 6) 3-piece sectional design, 7) Recessed receiver flange on both sides, 8) Tri-Cell backing on all walls, 9) Factory installed Armor Core Easy Base, 10) 5/8" threshold.

OPTIONAL ACCESSORIES:

Factory Plumbing Install Option: YES NO

PB Pressure Balancing Mixing Valve (ADA / ANSI)

HH Hand held shower assembly with slide bar, vacuum breaker and 60' hose (ADA / ANSI)



THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 40 1/4" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALLOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSURE.

NOTE: THIS UNIT WILL NOT ACCEPT A DOOR.

Job Name	Approved By Print Name	Date	COMFORT DESIGNS	
Project No	Approved By Signature		Model No. XSS 3637 BF 3P .625	
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com	Architect		Drawing No. XSS 3637 BF 3P .625 WLB WVB FHDP RRF WCR Tri-Cell Easy Base	
	Engineer		Date Issued. 4-3-12	Drawing Rev. 4-6-17
	Rep		Material. Acrylic Surface	
	Wholesaler		Color:	
Comments			Dimensions are in inches. Due to the nature of the materials dimensions may vary ± 1/2"	