


FRONT VIEW




SUBMITTAL


This tub shower enclosure shall be model SST 6032 TS left or right. Finished surface shall be of a sanitary grade solid surface exhibiting a minimal thickness of 55 dry mills and a finished cured Barcoal hardness of 80-90 as tested with ASTM D-2583. Unit construction shall be of a molded reinforced fiberglass with a 15% minimum fiberglass content.

The unit shall have outside dimensions of 60" x 33" x 77". The unit shall meet ANSI Z124.1-2, HUD, BOCA, NAHB, UPC, CSA, and shall meet the requirements of the Southern Building Code.

SIDE VIEW



TOP VIEW



The enclosure shall be equipped with the following accessories:

- 1) tile finish,
- 2) diamond accents,
- 3) molded soap ledge low in the corner at the drain end,
- 4) one inch diameter, 18 gauge stainless steel curtain rod with receiver cups,
- 5) tri cell backing on walls.

THIS UNIT FEATURES THE OUTSIDE DIMENSION OF 60" OF OVERALL WIDTH. THIS DOES NOT ALLOW FOR FULL ENCLOSURE OF THE BOLTS AND NUTS USED TO SECURE THE BARS AND SEAT IN PLACE. THE BOLT AND NUT COMBINATION SHOULD NOT PROTRUDE MORE THAN 3/4" ON EITHER SIDE OF THE SHOWER WALLS. THIS MAY REQUIRE THE NEED TO NOTCH STUDS TO ALLOW BOLT CLEARANCE FOR A DRYWALL ENCLOSED FIRE WALL INSTALLATION. ADJUSTMENT OF THE WALL BOARD MAY BE NECESSARY TO PROVIDE CLEARANCE OF THE BOLT(S) WHILE MAINTAINING THE INTEGRITY OF THE DRYWALL ENCLOSED FIRE WALL ENCLOSURE.

Job Name	Approved By	Name	Date	COMFORT DESIGNS		
Project No	Architect			Model No. SST 6032 TS-I		
Comfort Designs 435 Industrial Road Savannah, TN 38372 tel 800.443.7269 fax 731.925.4290 www.comfortdesignsbathware.com	Engineer			Drawing No. SST 6032 TS CR		
	Rep			Date Issued. 4-9-12	Drawing Rev.	
	Wholesaler			Material. Solid Surface		
	Comments			Color.		
				Dimensions are in inches. Due to the nature of the materials dimensions may vary ± 1/2"		